



20/40 EXTENDABLE CHASSIS

Overall Length	Closed - 29'06"; Open - 40'06"
Overall Width	96"
Coupler Height	48"
Kingpin Setting	24" from front of trailer
Weight	7,400 lbs. +/- 3%
Suspension	Spring Ride - 9700 Fixed Undermount Hutch
Axles	22,500lb capacity with synthetic wheel-end lubricant
Tires	11R22.5
Wheels	Steel HUB Pilot 22.5 x 8.25 white
Brakes	16-1/2" x 7"
ABS	Wabco 2 Sensor / 1 Modulator
Upper Coupler	AAR Certified Coupler with 5/16" 5th Wheel Plate
Main Frame	High tensile steel main beams
Cross Members	Fabricated steel channels
Bolsters	Fabricated 7-3/4" x 7-3/8" wide channel w/ steel casting end plates
Twist Locks	Retractable 3690-R Bufferes
Landing Gear	A420 T1 17 JOST w/ 10"x10"x2" low profile sandshoe
Lights	Sealed LED lights with a fully sealed wiring harness and internal ground
Electrical	Metal housing 7-way split pin Tectran
Air Connections	Fixed 90-degree 9296E Tectran

"Your Capacity Problem Solving Partner"

Headquarters: 1976 Auction Road Manheim, PA 17545
 Secondary Location: 15 Hershey Road Shippensburg, PA 17257
 Visit us at PennStroLeasing.com