



23.5' EXTENDABLE CHASSIS

- Made in the U.S.A.
- 6,600lbs
- 54,000lb **GVWR**
- Spring Ride Suspension
- Carries (1) 20' **ISO** Container

INTRODUCING the 23.5' Cheetah Extendable Chassis, the standard spec chassis carries (1) 20' ISO container. The 44" sliding bogie allows for greater carrying capacity. 160,000 lbs static load capacity to

be exact.

CONTACT

717.492.2665

sales@pennstroleasing.com

"Your Capacity Problem Solving Partner"

Headquarters: 1976 Auction Road Manheim, PA 17545 Shippensburg Branch: 15 Hershey Road Shippensburg, PA 17257 Visit us at PennStroLeasing.com





23.5' EXTENDABLE CHASSIS

Overall Length	Closed - 23' 3"; Open - 26' 11"
Overall Width	96"
Coupler Height	49"
Kingpin Setting	15" from front of chassis
Weight	6,600 lbs. +/- 3%
Suspension	Spring Ride
Axles	Two Axles, 49" Centers
Tires	11Rx22.5
Wheels	8.25" x 22.5 hub piloted tubeless
Brakes	2SIM, auto slacks, 30/30 brake chambers
Upper Coupler	5/16" pick up plate
Main Frame	Wide flange I-Beam, 2" deep, 19lb/ft, hot rolled steel, ASTM A572-50
Cross Members	All cross members are formed from 10-gauge steel
Bolsters	Box type w/ 3/8" x 8" top plate and 1/4" thick, formed channel lower member
Twist Locks	Meets ISO standards and requirements
Landing Gear	Two speed AAR approved, square leg, 55,000lbs lift capacity, 160,000lbs static load capacity, 10" x 10" low profile sandshoe, Curbside handle
Lights	Flange mounted LED light
Electrical	12 volt; 7 Way split pin receptacle plug; modular wiring harness

"Your Capacity Problem Solving Partner"

Headquarters: 1976 Auction Road Manheim, PA 17545 Secondary Location: 15 Hershey Road Shippensburg, PA 17257 Visit us at PennStroLeasing.com