


**53' FLATBED SLIDING TANDEM**

- 1** Lightweight Combo
- 2** Center Coil Package
- 3** Stainless Steel Corners
- 4** Sliding Axles
- 5** Low Rolling Resistance Tires

- 
- **INTRODUCING** the Utility flatbed: strength, toughness.
- durability. This flatbed is unparalleled in performance and
- productivity. Built with plasma-cut one-piece main beam
- webs, the Utility flatbed is a high strength aluminum/steel
- combo flatbed with an 80,000 pound distributed-load
- rating. Whatever you're hauling,
- get it there in confidence.



**CONTACT**  
**MATT FLOWER**  
 Director of Sales  
 717.492.2665  
[MFlower@PennStroLeasing.com](mailto:MFlower@PennStroLeasing.com)



*"Your Capacity Problem Solving Partner"*

Headquarters: 1976 Auction Road Manheim, PA 17545  
 Shippensburg Branch: 15 Hershey Road Shippensburg, PA 17257  
 Visit us at [PennStroLeasing.com](http://PennStroLeasing.com)



## 53' FLATBED SLIDING TANDEM

Outside Length	53'
Outside Width	102"
Coupler Height	47"
Deck Height	59 1/2"
Kingpin Setting	30"
Weight	Spring Ride: 10,895 lbs. (+/- 3%); Air Ride: 11,430 lbs. (+/- 3%)
Suspension	Spring or Air Ride Available
Axles	Hendrickson 23,000 lb. Capacity
Tires	275/80R 22.5 (75mph rated)
Wheels	Steel 22.5 x 8.25 HUB
Brakes	16-1/2 x 7" Quick-change Brake Shoes
ABS	2 Sensor / 1 Modulator
Main Frame	Plasma Cut One Piece Main Beam
Cross Members	3" Steel I-Beam Cross Members on 12" Center Line Full Length
Floor	1-1/8" Extruded Aluminum Flat Top Floor w/ 4 Hardwood Nail Strips
Bulkhead	Available Upon Quote
Payload Capacity	73,000 lbs. GVWR
Landing Gear	AAR Certified, 2 Speed Landing Gear w/ Tilt-cushion Sand Shoes
Lights	L.E.D.
Electrical	7 Way ATA Plug w/ No Circuit Breakers
Air Connections	Phillips Quik-E Gladhand w/ Quick Release Valve

*"Your Capacity Problem Solving Partner"*

Headquarters: 1976 Auction Road Manheim, PA 17545  
 Secondary Location: 15 Hershey Road Shippensburg, PA 17257  
 Visit us at [PennStroLeasing.com](http://PennStroLeasing.com)